



DH25 - 25 LITROS



DH50 - 50 LITROS



DH200 - 200 LITROS


DH1000
DH1000.2 -1000 LITROS

CARACTERÍSTICAS

Algunos materiales necesitan una temperatura constante durante el invierno o no deben bajar nunca de determinadas temperaturas. Para ello se han creado las bandas calefactoras de KRS. Gracias al núcleo radiante instalado en el interior de las bandas, los materiales pueden mantener siempre la temperatura ideal requerida por el usuario. Cada banda está equipada con un termostato integrado que permite regular la temperatura interna de la banda entre 0 y 90 °C. El usuario calibrará el termostato en función del tiempo y las características del material del recipiente y de su contenido. La banda está compuesta por un revestimiento exterior de nailon, un material sintético muy resistente y duradero incluso en las condiciones más extremas. En su interior tiene una capa aislante de fibra de vidrio, a la que se fija la resistencia. Todo ello está recubierto con una capa de vidrio-silicona, ideal para adherirse perfectamente al barril o palé que el usuario debe calentar y resistir las altas temperaturas. Toda la fabricación se realiza en Italia. La potencia de cada una de las bandas calefactoras para barriles varía entre 400 y 550 W/m²

CARACTERÍSTICAS	UNIDAD	DH25	DH50	DH200	DH1000 DH1000.2
ALIMENTACIÓN	V AC	230	230	230	230
POTENCIA	Watt	130	220	650	1X2000 RESISTENZA SINGOLA 2X1000 RESISTENZA DOPPIA
TERMOSTATO	-	INCORPORADO AJUSTABLE 0-150 °C	INCORPORADO AJUSTABLE 0-150 °C	INCORPORADO AJUSTABLE 0-150 °C	INCORPORADO AJUSTABLE 0-150 °C
MATERIAL	-	EXTERIOR: CORDURA INTERIOR: TEJIDO DE FIBRA DE VIDRIO RECUBIERTO DE GOMA SILICONADA	EXTERIOR: CORDURA INTERIOR: TEJIDO DE FIBRA DE VIDRIO RECUBIERTO DE GOMA SILICONADA	EXTERIOR: CORDURA INTERIOR: TEJIDO DE FIBRA DE VIDRIO RECUBIERTO DE GOMA SILICONADA	EXTERIOR: CORDURA INTERIOR: TEJIDO DE FIBRA DE VIDRIO RECUBIERTO DE GOMA SILICONADA
DIMENSIONES	H mm	400 X CIRCUNFERENCIA 1200	460 X CIRCUNFERENCIA 1330	800 X CIRCUNFERENCIA 1990	1000 X CIRCUNFERENCIA 4400
IP	-	40	40	40	40
CABLE DE ALIMENTACIÓN	MT	SILICÓNICO - 3 SIN ESPINA	SILICÓNICO - 3 SIN ESPINA	SILICÓNICO - 3 SIN ESPINA	SILICÓNICO - 3 SIN ESPINA
TAPA	-	NO	NO	NO	AISLADO PARA UN MEJOR RENDIMIENTO Y MENORES TIEMPOS DE CALENTAMIENTO



DH25 - 25 LITERS



DH50 - 50 LITERS



DH200 - 200 LITERS


DH1000
DH1000.2 -1000 LITERS

CHARACTERISTICS

Some materials need a constant temperature during winter or should never drop below certain temperatures. For this purpose, KRS heating bands have been created. Thanks to the radiant core installed inside the bands, the materials can always maintain the ideal temperature required by the user. Each band is equipped with an integrated thermostat that allows the internal temperature of the band to be adjusted between 0 and 90 °C. The user will calibrate the thermostat based on time and the characteristics of the container material and its contents. The band is composed of a nylon outer coating, a synthetic material very resistant and durable even in the most extreme conditions. Inside it has an insulating layer of fiberglass, to which the resistance is attached. All of this is covered with a glass-silicone layer, ideal for perfectly adhering to the barrel or pallet that the user must heat and withstand high temperatures. All production is carried out in Italy. The power of each of the heating bands for barrels varies between 400 and 550 W/m 2

TECHNICAL SPECIFICATIONS	UNIT	DH25	DH50	DH200	DH1000 DH1000.2
POWER SUPPLY	V AC	230	230	230	230
POWER	Watt	130	220	650	1 × 2000 SINGLE HEATING ELEMENT 2 × 1000 DOUBLE HEATING ELEMENT
THERMOSTAT	-	BUILT-IN, ADJUSTABLE 0-150 °C	BUILT-IN, ADJUSTABLE 0-150 °C	BUILT-IN, ADJUSTABLE 0-150 °C	BUILT-IN, ADJUSTABLE 0-150 °C
MATERIAL	-	OUTER: CORDURA INNER: FIBREGLASS FABRIC RUBBER-COATED SILICONE-COATED	OUTER: CORDURA INNER: FIBREGLASS FABRIC RUBBER-COATED SILICONE-COATED	OUTER: CORDURA INNER: FIBREGLASS FABRIC RUBBER-COATED SILICONE-COATED	OUTER: CORDURA INNER: FIBREGLASS FABRIC RUBBER-COATED SILICONE-COATED
DIMENSIONS	H mm	400 × 1200 CIRCUMFERENCE	460 X 1330 CIRCUMFERENCE	800 X 1990 CIRCUMFERENCE	1000 X 4400 CIRCUMFERENCE
IP	-	40	40	40	40
POWER CABLE	MT	SILICONE - 3 WITHOUT PLUG	SILICONE - 3 WITHOUT PLUG	SILICONE - 3 WITHOUT PLUG	SILICONE - 3 WITHOUT PLUG
LID	-	NO	NO	NO	INSULATED FOR IMPROVED EFFICIENCY AND REDUCED HEATING TIMES