



FDK44

CARACTERÍSTICAS

- Alta capacidad de secado.
- Estructura metálica robusta.
- Control electrónico.
- Horas de funcionamiento.
- Muy silenciosos.
- Plug and play.
- Pantalla digital para el ajuste de la humedad.
- Reinicio automático tras un corte de corriente.
- Filtro de aire lavable.
- Bajo consumo eléctrico



FDK100

CARACTERÍSTICAS	UNIDAD	FDK44	FDK100
CAUDAL DE AIRE	m3/h	450	1100
CAPACIDAD A 30°C / 80%	l/h	36/24	80/24
REFRIGERANTE	-	R410a	R410a
CAMPO DE TRABAJO	C°	1-35	1-35
ALIMENTACIÓN ELÉCTRICA	V/Ph/Hz	230/1/50	230/1/50
TIPO DE CONEXIÓN	-	SCHUKO	SCHUKO
POTENCIA MÁX. ABSORBIDA	W	570	1050
CORRIENTE MÁX. ABSORBIDA	A	3.9	7.2
RUMOROSIDAD	dB	51	56
DESCARGA DIRECTA DE AGUA	-	SI	SI
DIMENSIONES	mm	350X420X580	516X516X656
PESO	Kg	34	48



FDK44

CHARACTERISTICS

- High drying capacity
- Sturdy metal construction
- Electronic control
- Hours of operation
- Very quiet
- Plug and play
- Digital display for humidity regulation
- Automatic restart after power failure
- Washable air filter
- Low power consumption



FDK100

CHARACTERISTICS	UNIT'	FDK44	FDK100
AIR FLOW	m3/h	450	1100
CAPACITY AT 30°C / 80%	l/h	36/24	80/24
REFRIGERATOR	-	R410a	R410a
WORK CAMP	C°	1-35	1-35
POWER SUPPLY	V/Ph/Hz	230/1/50	230/1/50
CONNECTION TYPE	-	SCHUKO	SCHUKO
MAX. POWER ABSORBED	IN	570	1050
MAX. CURRENT ABSORBED	A	3.9	7.2
NOISE	dB	51	56
DIRECT WATER DISCHARGE	-	YES	YES
DIMENSIONS	mm	350X420X580	516X516X656
WEIGHT	Kg	34	48