



KÄFER 180 R

CARACTERÍSTICAS

- Estructura metálica recubierta de polvo epoxi
- Quemador de acero inoxidable
- Caja de mandos en material termoplástico
- con grado de aislamiento IP44
- Controles de seguridad de la llama realizados través termocopia, termostato electroválvula
- Encendido piezoeléctrico
- Motor con protección térmica
- Adecuado para entornos abiertos y semiabiertos

CARACTERÍSTICAS	UNIDAD	KÄFER 180 R
POTENCIA TÉRMICA	kW Kcal/H btu/H	16-30 13.760-25.800 54.593-102.362
CAUDAL DE AIRE	m3/H	650
POTENCIA ABSORBIDA	Watt	80
ALIMENTACIÓN ELÉCTRICA	ph-volt/Hz	1-230/50
CONSUMO DE COMBUSTIBLE	Kg/h	1.12-2.1
PRESIÓN DE COMBUSTIBLE	bar/psi	1.5-21-75
TIPO DE COMBUSTIBLE	-	G30-31 PROPANO BUTANO
DIMENSIONES	mm	240X270X535
PESO	Kg	7..9



KÄFER 180 R

CHARACTERISTICS

- Metal structure painted with epoxy powders
- Stainless steel burner
- Control box in thermoplastic material with IP44 insulation rating
- Flame safety checks performed via thermocouple, thermostat and solenoid valve
- Piezoelectric ignition
- Motor with thermal protection
- Suitable for open and semi-open spaces

TECHNICAL SPECIFICATIONS	UNIT	KÄFER 180 R
THERMAL OUTPUT	kW Kcal/H btu/H	16-30 13.760-25.800 54.593-102.362
AIRFLOW	m3/H	650
POWER INPUT	Watt	80
POWER SUPPLY	ph-volt/Hz	1-230/50
FUEL CONSUMPTION	Kg/h	1.12-2.1
FUEL PRESSURE	bar/psi	1.5-21-75
FUEL TYPE	-	G30-31 PROPANE BUTANE
DIMENSIONS	mm	240X270X535
WEIGHT	Kg	7..9