



KRS MODEL HE09R



CARACTERÍSTICAS

Los generadores eléctricos KRS están fabricados en acero inoxidable y todos los dispositivos ofrecen doble protección contra el sobrecalentamiento. La temperatura se puede ajustar mediante el termostato integrado con tres niveles de potencia seleccionables para una máxima comodidad. La clasificación de impermeabilidad es IP24 para un uso seguro incluso en entornos húmedos y mojados. El mango está fabricado en plástico aislante y la carcasa metálica está recubierta con polvo antioxidante. El sistema se apaga en caso de sobrecalentamiento. El modelo HE09R cuenta con inclinación ajustable verticalmente

NECESARIAS:

HE09R → 4 polos 16 A - 380V

CARACTERÍSTICAS	UNIDAD	HE09R
POTENCIA	kW	9
ALIMENTACIÓN ELÉCTRICA	V/Hz	400/ 3-50
POTENCIAS SELECCIONABLES	W	60 4.500 9.000
IP	-	24
CAUDAL DE AIRE	m ³ /H	760
DIMENSIONES	m ²	330x330x400
PESO	Kg	8.2



KRS MODEL HE09R



CHARACTERISTICS

KRS electric heaters are made of stainless steel, and all units offer double protection against overheating.

The temperature can be set via the integrated thermostat, with three selectable power levels to ensure maximum comfort.

The ingress protection rating is IP24, allowing safe use even in humid and wet environments.

The handle is made of insulated plastic, and the metal housing is coated with anti-rust powder paint. Automatic shut-off system in case of overheating. Model HE09R is equipped with vertically adjustable tilt.

REQUIRED:

HE09R → 4 pole 16 A - 380V

TECHNICAL SPECIFICATIONS	UNIT	HE09R
POWER	kW	9
POWER SUPPLY	V/Hz	400/ 3-50
SELECTABLE POWER LEVELS	W	60 4.500 9.000
IP	-	24
AIRFLOW	m ³ /H	760
DIMENSIONS	m ²	330x330x400