



AX 10
AX 15
AX 21

CARACTERÍSTICAS

- Los modelos **AX10/15/21** tienen una estructura resistente totalmente metálica que garantiza un rendimiento a alta velocidad.
- La inclinación ajustable de 180° permite un control preciso del flujo de aire.
- Las ruedas de goma de alta resistencia y el asa de fácil agarre garantizan una movilidad fluida. Las robustas palas de aluminio garantizan un flujo de aire potente y duradero con un mantenimiento mínimo.
- Ideales para talleres, garajes, fábricas y otros entornos industriales exigentes.

CARACTERÍSTICAS	UNIDAD	AX10	AX15	AX 21
CAUDAL DE AIRE VELOCIDAD MÁXIMA	m3/h	9.900	17.100	21.600
CAUDAL DE AIRE VELOCIDAD MEDIA	m3/h	8.550	15.600	19.920
CAUDAL DE AIRE VELOCIDAD MÍNIMA	m3/h	7.200	13.500	17.400
ALIMENTACIÓN ELÉCTRICA	v/Hz	220/240/50	220/240/50	220/240/50
POTENCIA ABSORBIDA VELOCIDAD MÁXIMA	W	180	315	630
CORRIENTE ABSORBIDA VELOCIDAD MÁXIMA	Amp	1.7	3	4
DIMENSIONES	mm	700x700x300	910x935x350	1090x380x1130
DIMENSIONES DEL VENTILADOR	mm	600	750	900
PESO	Kg	10	24.5	33



AX 10
AX 15
AX 21



CHARACTERISTICS

- The **AX10/15/21** feature a robust, all-metal structure ensuring high-speed performance.
- The adjustable 180° tilt allows precise control of airflow.
- Heavy-duty rubber wheels and an easy-grip handle ensure smooth mobility.
- The durable aluminium fan blades provide powerful and long-lasting airflow with minimal maintenance.
- Ideal for workshops, garages, factories, and other demanding industrial environments.

TECHNICAL SPECIFICATIONS	UNIT	AX10	AX15	AX 21
AIRFLOW – MAX. SPEED	m3/h	9.900	17.100	21.600
AIRFLOW – AVERAGE SPEED	m3/h	8.550	15.600	19.920
AIRFLOW – MINIMUM SPEED	m3/h	7.200	13.500	17.400
POWER SUPPLY	v/Hz	220/240/50	220/240/50	220/240/50
POWER INPUT – MAX. SPEED	W	180	315	630
CURRENT INPUT – MAX. SPEED	Amp	1.7	3	4
DIMENSIONS	mm	700x700x300	910x935x350	1090x380x1130
DIMENSIONS FAN	mm	600	750	900
WEIGHT	Kg	10	24.5	33