



WF2.5
WF5.0
WF10

CARACTERÍSTICAS

Warmfoam, compuesto por una esponja de polietileno de 5 mm, es ideal para todo tipo de aplicaciones. Gracias a su grosor y a las características del material, es extremadamente ligero, por lo que se puede transportar cómodamente en rollos de 1 metro de altura. La esponja de polietileno tiene la función de proporcionar estabilidad mecánica al sistema y garantiza el efecto antirruido y antideslizante

CARACTERÍSTICAS	UNIDAD	PANEL
ESPESOR	mm	5
PESO	Kg/m ²	0.030
VALOR	m ² .K.W-1	0.19
DENSIDAD	Kg/m ³	30+/-3
CARGA DE ROTURA LONGITUDINAL	N/mm ²	>0.18
CARGA DE ROTURA TRANSVERSAL	N/mm ²	>0.16
TEMPERATURA DE USO	C°	-40/+95
PERMEABILITA' AL VAPORE ACQUEO	ng/Pa s m	0.12
CONDUCTIVIDAD TÉRMICA	Kcal/h m C°	0.0340

MODELO	AREA (m ²) - DIMENSIONES(m)
WF2.56	2.5/1X2.5
WF5.0	5.0/1X5
WF10	10/1X10

PERMEABILIDAD AL VAPOR DE AGUA



WF2.5
WF5.0
WF10

CARATTERISTICHE

Warmfoam, made of a 5 mm polyethylene foam, is ideal for all types of applications. Thanks to its thickness and material properties, it is extremely lightweight and can therefore be easily transported in 1 m high rolls.

The polyethylene foam provides mechanical stability to the system and ensures effective noise reduction and anti-footfall performance.

TECHNICAL SPECIFICATIONS	UNIT	PANEL
THICKNESS	mm	5
WEIGHT	Kg/m ²	0.030
VALUE	m ² .K.W-1	0.19
DENSITY	Kg/m ³	30+/-3
LONGITUDINAL BREAKING LOAD	N/mm ²	>0.18
TRANSVERSE BREAKING LOAD	N/mm ²	>0.16
OPERATING TEMPERATURE	C°	-40/+95
WATER VAPOUR PERMEABILITY	ng/Pa s m	0.12
THERMAL CONDUCTIVITY	Kcal/h m C°	0.0340

MODEL	AREA (m ²) - DIMENSIONS (m)
WF2.56	2.5/1X2.5
WF5.0	5.0/1X5
WF10	10/1X10